





PC Board Layout





NOTES:

ELECTRICAL:

1.	VOLTAGE RATING	:125 VAC RMS.
2.	CURRENT RATING	: 1.5 AMP.
3.	CONTACT RESISTANCE	: 30 MILLIOHMSMAX
4.	INSULATION RESISTANCE	: 500 MEGOHMS MIN @ 500 NDC.
5.	DIELECTRIC STRENGTH	: 1000 VAC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

1.	HOUSING & INSERT MATERIAL	: PBT UL94V-0.
2.	CONTACT MATERIAL	: DIAMETER0.45MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
3.	MATING/UNMATING FORCE	: 2.2KG.F MAX.
4.	RETENTION STRENGTH	: 7.7KG.F MIN BETWEEN JACK AND PLUG.
5.	OPERATING LIFE	: 750 CYCLES MIN.

ENVIRONMENTAL:

1.	STORAGE	: -40℃ ～+85℃ REATIVE HUMIDITY<70%
2.	OPERATION	: -40℃ ～+85℃

DIMENSIONS TOLERANCE METRIC Up to 5 ±0.2 Above 5~15 ±0.3 Above 15~30 ±0.4 Above 30~50 ±0.5 Angle ±0.3°	UNITS	MM	FINISH	SEE NOTE	CH'K	Calvin	DRAW NAME RJ45 8P8C SIDE ENTRY JACK WITHOUT SHIELDED		WISCONN Technology Co.,Ltd Tel:+886-2-2790-1979 Fax:+886-2-2790-1569						
	QT'Y	N/A	DRAW	Johnson	APP'D	Selena	PART NUMBER	WRJ5HLP-88FPBDR-15.0							
	MT'L	SEE NOTE	DE'N	Mike	DATE	May . 17 . 2022	DRAW NUMBER	C006	SCALE	1/1	SIZE	A4	SHEET	1	REV. A
							FILE NAME .DWG								