



P.C.B. LAYOUT

MATERIALS:

1. Housing: PBT (UL 94V-0), Black
2. Contacts: Brass
3. Shell: SPCC
4. Board Lock: SPCC
5. Screw: SPCC(Lead ≤ 40000PPM)

FINISH:

1. Contacts: Gold Flash Plated on Contact Area
Sn Plated on Solderails
Nickel Under Plated Over All
2. Shell: Nickel Plated
3. Board Lock: Sn Plated
4. Screw: Nickel Plated

| | | | | | | | | | | | | | | | |
|--|-------|----------|--------|----------|-------|-------------|------------------------------|-------------------|---|-----|------|----|-------|---|------|
| DIMENSIONS TOLERANCE METRIC .0=±0.30 .00=±0.20 .000=±0.10 ANG.=±2° | UNITS | MM | FINISH | SEE NOTE | CH'K | Calvin | DRAW NAME | | WISCONN Technology Co., Ltd Tel:+886-2-2790-1979 Fax:+886-2-2790-1569 | | | | | | |
| | QT'Y | N/A | DRAW | Johnson | APP'D | Selena | D-SUB 8.08mm Female 半金叉鎖 90度 | | | | | | | | |
| | MT'L | SEE NOTE | DE'N | Mike | DATE | DEC.26.2017 | PART NUMBER | WDBF-xxFPBDR-8.08 | | | | | | | |
| | | | | | | | DRAW NUMBER | T039 | SCALE | 1/1 | SIZE | A4 | SHEET | 1 | REV. |
| | | | | | | | FILE NAME .DWG | | | | | | | | |