



Note:

1.Material:

- 1.1 Housing: LCP UL 94-V0 rated.
- 1.2 Contact: Phosphor Bronze, t=0.20mm.
- 1.3 Front Shell: Stainless steel, t=0.20mm.
- 1.4 Back Shell: Stainless steel, t=0.20mm.
- 1.5 卡钩 : Stainless steel, t=0.40mm.

2.specification:

- 2.1 Current rating:1A MAX.
- 2.2 Dielectric withstanding voltage:500 v(ac) far minuta.
- 2.3 Contact resistance: 30 mΩ max.
- 2.4 Insulation resistance: 1000 MΩ min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C.

3.Finishes:

- 3.1 Contacts: Gold flashed, 1u",3u",5u",15u", 30u".on Contact area . 100u-120u" Tin. Plating on soldertails. 50u"-80u" Nickel .underplating over all

胶芯主体

BACK SHELL

FRONT SHELL

3	卡钩	2	Stainless steel	T=0.40±0.01mm		D3950XX-A
5	BACK SHELL	1	Stainless steel	T=0.20±0.01mm		D4480XX
4	FRONT SHELL	1	Stainless steel	T=0.20±0.01mm		D4510XX-A
2	CONTACT	5	Phosphor Bronze	T=0.20±0.01mm	Gold flashed	A4520XX-A A4520XX
1	HOUSING	2	LCP		White/Black	JCH0139-A(主体)
No.	Part Name	Q'ty	Material	Thickness	Finish	Notes

DIMENSIONS TOLERANCE METRIC .0=±0.30 .00=±0.20 .000=±0.10 ANG.=±2°	單位(UNITS)	MM	處理(FINISH)	SEE NOTE	審校(CH'K)	Calvin	圖名(NAME) MICRO USB 5P A B MALE SOLDER		WISCONN Technology Co., Ltd Tel:02-2742-1798 Fax:02-2742-1898							
	數量(QT'Y)	N/A	繪圖(DRAW)	Johnson	核准(APP'D)	Selena	料號(PART NUMBER)	WMRU2-05FPB-SOLDER								
	材料(MT'L)	SEE NOTE	設計(DE'N)	Mike	日期 DATE)	OCT.15.2007	圖號(DRAW NUMBER)	T003	比例 (SCALE)	1/1	圖紙 (SIZE)	A4	頁次 (SHEET)	1	版次 (REV.)	A
								圖檔(FILE NAME .DWG)								