



SPECIFICATIONS

Electrical:

- 1.Current Rating: 0.5 A
- 2.Contact Resistance: 50 mΩ Max
- 3.Dielectric Withstanding Voltage: 100 V AC
- 4.Insulation Resistance: 100 MΩ Min

Material:

- 1.Housing: LCP,UL 94V-0,Black
- 2.Contact: Phosphor Bronze
- 3.Shell: Brass

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer

DIMENSIONS TOLERANCE METRIC .0=±0.30 .00=±0.20 .000=±0.10 ANG.=±2°	單位<UNITS>	MM	處理<FINISH>	SEE NOTE	審校<CH'K>	Calvin	圖名<NAME>		WISCONN Technology Co., Ltd Tel:02-2742-1798 Fax:02-2742-1898					
	數量<QT'Y>	N/A	繪圖<DRAW>	Johnson	核准<APP'D>	Selena	MICRO USB2.0 5P B TYPE SMT MALE 180度							
	料號<PART NUMBER>	WMRU2M-5-xxVS	圖號<DRAW NUMBER>	T002	圖檔<FILE NAME .DWG>		比例<SCALE>	1/1	圖紙<SIZE>	A4	頁次<SHEET>	1	版次<REV.>	A
	材料<MT'L>	SEE NOTE	設計<DE'N>	Mike	日期<DATE>	MAR.26.2015								