



**1.characteristics:**

- 2.1 Rating Voltage : 30V AC.
- 2.2 Rating Current:1 AMP
- 2.3 Contact Resistance:30 mΩ MAX.
- 2.4 Insulation Resistance:100 MΩ MIN.
- 2.5 Withstanding Voltage:AC 500V.
- 2.6 Mating force: 3.57Kgf MAX(35N MAX)
- 2.7 Extraction force:1Kgf Min(9.8N Min)
- 2.8 Life test:1500Cycles MIN.
- 2.9 Temperature Range: -30℃~ +80℃.

**2.MATERIAL:**

- 1.1 Housing:PBT+30%G.F UL94V-0, Color:White/Black.
- 1.2 Contact1:COPPER ALLOY,T=0.25mm
- 1.3 Shell:Copper Alloy/SPCC,T=0.30mm

DIMENSIONS TOLERANCE <b>METRIC</b> .0=±0.30 .00=±0.20 .000=±0.10 <b>ANG.=±2°</b>	單位(UNITS)	MM	處理(FINISH)	SEE NOTE	審核(CH'K)	Calvin	圖名(NAME)		WISCONN Technology Co.,Ltd Tel:02-2742-1798 Fax:02-2742-1898									
	數量(QT'Y)	N/A	繪圖(DRAW)	Johnson	核准(APP'D)	Selena	USB A Female R/A(正向90°)											
	材料(MT'L)	SEE NOTE	設計(DE'N)	Mike	日期 (DATE)	OCT.15.2007	料號(PART NUMBER)	WU2AF-04FPWDR-C	圖號(DRAW NUMBER)	C002	比例 (SCALE)	1/1	圖紙 (SIZE)	A4	頁次 (SHEET)	1	版次 (REV.)	A
	圖檔(FILE NAME .DWG)																	