



SPECIFICATIONS

Electrical:

1. Rated Voltage: 30V AC / DC
2. Rated Current: 1.5 A Max
3. Dielectric Withstanding Voltage: AC 500 V / 1MIN
4. Insulation Resistance: 1,000 MΩ Min
5. Contact Resistance: 30 mΩ Max

Material:

1. Housing: PBT
2. Contact: Brass
3. Shell: Brass / SPCC

Finish:

1. Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls
Nickel under plated overall
2. Shell: Nickel under Plated surface layer

PCB LAYOUT MOUNTING PATTERN

DIMENSIONS TOLERANCE METRIC .0±0.30 .00±0.20 .000±0.10 ANG.=±2°	單位(UNITS)	MM	處理(FINISH)	SEE NOTE	審校(CH'K)	Calvin	圖名(NAME)		WISCONN Technology Co., Ltd Tel:02-2790-1979 Fax:02-2790-1569								
	數量(QTY)	N/A	繪圖(DRAW)	Johnson	核准(APP'D)	Selena	料號(PART NUMBER)						WU2AF-4-FWIU1-S14				
	材料(MT'L)	SEE NOTE	設計(DE'N)	Mike	日期 DATE)	MAY.23.2016	圖號(DRAW NUMBER)		T002		比例(SCALE)	1/1	圖紙(SIZE)	A4	頁次(SHEET)	1	版次(REV.)