



**Note:**

**1.Material:**

- 1.1 Insulator: LCP/PBT UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Cold rolled steel,t=0.30mm.

**2.Specification:**

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 MΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C.

**3.Finishes:**

- 3.1 Contacts: Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel plated.

|  |           |          |            |          |           |             |                                      |                    |  |     |          |    |           |   |          |   |
|--|-----------|----------|------------|----------|-----------|-------------|--------------------------------------|--------------------|--|-----|----------|----|-----------|---|----------|---|
| DIMENSIONS TOLERANCE<br><u>METRIC</u><br>.0=±0.30<br>.00=±0.20<br>.000=±0.10<br>ANG.=±2° | 單位(UNITS) | MM       | 處理(FINISH) | SEE NOTE | 審核(CH'K)  | Calvin      | 圖名(NAME)<br>USB 2.0 AM PLUG SMT(青蛙腳) |                    | <b>WISCONN Technology Co., Ltd</b><br>Tel:02-2742-1798- Fax:02-2742-1898 |     |          |    |           |   |          |   |
|  | 數量(QT'Y)  | N/A      | 繪圖(DRAW)   | Johnson  | 核准(APP'D) | Selena      | 料號(PART NUMBER)                      | WU2AM-04FLBSRF-5.7 |  |     |          |    |           |   |          |   |
|  | 材料(MT'L)  | SEE NOTE | 設計(DE'N)   | Mike     | 日期 DATE)  | OCT.15.2007 | 圖號(DRAW NUMBER)                      | T003               | 比例(SCALE)  | 1/1 | 圖紙(SIZE) | A4 | 頁次(SHEET) | 1 | 版次(REV.) | A |
|  |           |          |            |          |           |             |                                      | 圖檔(FILE NAME .DWG) |  |     |          |    |           |   |          |   |