



MATERIAL:
 INSULATOR : THERMOPLASTICS, UL94V-0.
 CONTACT : COPPER ALLOY.
 CONTACT FINISH : GOLD ON MATING END, TIN ON TERMINATION END,
 WITH ENTIRE CONTACT NICKEL UNDERPLATED.
 FRONT SHELL : BRASS, NICKEL PLATED.
 MIDDLE SHELL : BRASS OR STAINLESS STEEL, NICKEL PLATED.
 BACK SHELL : BRASS OR SPCO, NICKEL PLATED.

SPECIFICATION:
 CURRENT RATING : 1 AMP.
 DIELECTRIC WITHSTANDING VOLTAGE : 500V AC FOR 1 MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN.
 CONTACT RESISTANCE : 30mΩ MAX.
 OPERATING TEMPERATURE : -40°C ~ +105°C.

DIMENSIONS TOLERANCE METRIC .0=±0.30 .00=±0.20 .000=±0.10 ANG.=±2°	單位(UNITS)	MM	處理(FINISH)	SEE NOTE	審核(CH'K)	Calvin	圖名(NAME)		WISCONN Technology Co., Ltd Tel:02-2742-1798 Fax:02-2742-1898							
	數量(QTY)	N/A	繪圖(DRAW)	Johnson	核准(APP'D)	Selena	USB3.0 STACKED A/F R/A DIP BLUE									
	材料(MT'L)	SEE NOTE	設計(DE'N)	Mike	日期(DATE)	OCT.15.2007	料號(PART NUMBER)	WU3AF-2X1xxNBUDR								
							圖號(DRAW NUMBER)	T013		比例(SCALE)	1/1	圖紙(SIZE)	A4	頁次(SHEET)	1	版次(REV.)