



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 TERMINAL: PHOSPHOR BRONZE, GOLD PLATED ON CONTACT
 AREA TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C

PIN NO.	NAME
C1	Vcc
C2	RST
C3	CLK
C5	GND
C6	Vpp
C7	I/O

DIMENSIONS TOLERANCE METRIC .0=±0.30 .00=±0.20 .000=±0.10 ANG.=±2°	單位(UNITS)	MM	處理(FINISH)	SEE NOTE	審核(CH'K)	Calvin	圖名(NAME) SIM CARD 6PIN PCB MOUNT SMT HINGE TYPE WITH POST	WISCONN Technology Co., Ltd Tel:02-2742-1798 Fax:02-2742-1898								
	數量(QTY)	N/A	繪圖(DRAW)	Johnson	核准(APP'D)	Selena						料號(PART NUMBER)	WSIM-06FHTBSR-C			
	材料(MTL)	SEE NOTE	設計(DE'N)	Mike	日期 DATE)	NOV.06.2014	圖號(DRAW NUMBER)	T004	比例 (SCALE)	1/1	圖紙 (SIZE)	A4	頁次 (SHEET)	1	版次 (REV.)	A
								圖檔(FILE NAME .DWG)								